> Hydraulic COMPACT OD 99T BP





DESCRIPTION

- > Delayed action
- ► Low pressure
- ➤ Compact with telescopic adjustment
- Can be installed into ceramic or plastic cisterns, recessed or low level cisterns, for replacement or as original equipment
- ► Hydraulic closure (no water hammer shock)
- ➤ Adjustable water level
- ➤ Quiet
- ➤ Anti-backflow function
- ➤ From 0.1 to 10 bar
- ► Flow rate 0.23l/s at 3 bars
- ➤ 1/2" brass

DELAYED ACTION MECHANISM



The cistern empties quicker than the water in the delaying case, keeping the inlet valve closed.



Once the flush is complete and the flush valve closes, the delaying case keeps draining water which then allows the inlet valve open and refill the cistern.

TEXT FOR TENDERS:

COMPACT OD 99T BP **WRAS**

Bottom entry inlet valve with 1/2" brass connection WRAS certified and 10-year-guarantee. Features: delayed action, adjustable height, low pressure, quiet, hydraulic closure, adjustable water level and anti-back flow. Length 270mm, width 112mm, deepth 50mm.

	Ref.	Barcode	Packing	Packing			Pallet
	nei.			Nb	М³	Kg	quantity
COMPACT OD 99T BP Low Pressure 1/2" Brass Delayed Action	30 9923 10	3 24723 006954 5	Box	24	0.08	9.7	360

*Based upon a 4-people-family consumption when replacing a standard inlet valve



